

## DEKA Aluminium Inground Light



### Description

The DEKA luminaire provides a practical solution for all inground lighting applications including pathways, driveways, courtyards and decks. Utilising a solid brass CNC machined external fascia plate and a 6063 graded aluminium in a black anodised finish.

The DEKA recessed inground luminaire in anodised aluminium finish will last the test of time. A polycarbonate housing is provided for concrete applications. For installations in which do not require the polycarbonate housing such as timber decks the stainless steel spring clips offer a secure fit. Idea applications would also include up lighting trees, feature garden wall, external house fascia etc.



### Specification Features

Input Voltage:	12V DC
Power (W):	3W
IP rating (IP):	65
Lumens (lm):	Warm White 3000K - 300lm White 5000K - 350lm
LED type:	CREE
CCT:	3000K - 5000K
CRI:	≥83
Beam angle (°):	60°
Dimmable:	No
Lifespan (hrs):	50,000hrs
Cutout (Ø):	Ø77mm
Drive over:	2000kgs (19424, 19426)

### Body

Order Code:	19458
Product Code:	DEKA-BODY-3K
Colour:	Warm White - 3000K
Order Code:	19459
Product Code:	DEKA-BODY-5K
Colour:	White - 5000K

### Aluminium Covers

Order Code:	19424
Product Code:	DEKA-COVER-RND-OPEN-ALU
Order Code:	19426
Product Code:	DEKA-COVER-SQR-OPEN-ALU
Order Code:	19428
Product Code:	DEKA-COVER-1-WAY-ALU
Order Code:	19430
Product Code:	DEKA-COVER-2-WAY-ALU
Order Code:	19432
Product Code:	DEKA-COVER-3-WAY-ALU
Order Code:	19434
Product Code:	DEKA-COVER-4-WAY-ALU
Order Code:	19436
Product Code:	DEKA-COVER-EYELID-ALU

### Diagrams / Additional

