

PANEL-312 WHT TRIO



Description

35W LED Panel light. White frame, opal diffuser. These are ideal as ceiling light for T-BAR ceilings, or by using a plaster recessed frame, ideal for commercial applications, office spaces. Now with TRIO, the added option of changing the colour temperature output of the panel with a dip switch function attached to the cable of the fitting.


Specification Features

Input Voltage:	240V
Power (W):	35W
IP rating (IP):	44
Lumens (lm):	Warm White 3000K - 3200lm
	Neutral White 4000K- 3300lm
	White 5700K - 3400lm
LED type:	High efficiency SMD LED
CCT:	3000K - 4000K - 5700K (Switchable)
CRI:	≥80
Dimmable:	No
Lifespan (hrs):	40,000hrs
Mounting type:	Recessed into standard grid ceiling or via optional plaster trim kit for plaster board ceilings or via optional wire suspended or surface mounted kit.

*DISCLAIMER: Please note our Three Year Warranty does not cover discolouration of the diffuser. Please see Instruction Manual for further details.



Diagrams / Additional



8mm height



Order Code:17609Product Code:PANEL-312-WHT-TRIOColour:White frame - 3000K-4000K-5700K (Switchable)



LED Panel Trim (Recessed Plaster Frame) Product Code: TRIM312-W Order Code: 19326



Product Code:SM-KIT312-AOrder Code:19330Colour:Aluminium Anodised

Product Code: SM-KIT312-W Order Code: 19334 Colour: Satin White

Domus Lighting 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com Specification subject to change without prior notice.



PANEL-312 Panel Light



Description

45W LED Panel light. Natural anodised aluminium frame, opal diffuser. These are ideal as ceiling light for T-Bar ceilings, or by using a plaster recessed frame, ideal for commercial applications such as office spaces. Fully dimmable with Domus dimmer series.



Specification Features

Input Voltage:	240VAC	
Power (W):	45W	
IP rating (IP):	44	
Lumens (lm):	Warm White 3000K - 3400lm Neutral White 4000K - 3000lm White 6000K - 3550lm	
LED type:	High efficiency SMD LED	
CCT:	3000К -4000К - 5000К	
CRI:	≥80	
Dimmable:	Yes*	
Mounting Type:	Recessed into standard grid ceiling or via optional plaster trim kit for plaster board ceilings or via optional wire suspended or surface mounted kit.	
Lifespan (hrs):	50,000hrs	
Dimensions:	(L) 1195mm x (W) 295mm x (H) 10mm	
* Dimmable when used in conjunction with the Domus dimmer series.		

May work with others but not tested.

Diagrams / Additional



Order Code:	19311		
Product Code:	PANEL-312-SLR-WW		
Colour:	Warm White LED 3000K		
Order Code:	19310		
Product Code:	PANEL-312-SLR-NW		
Colour:	Neutral White LED 4000K		
Order Code:	19309		
Product Code:	PANEL-312-SLR-W		
Colour:	White LED 6000K		
LED Panel Trim (Recessed Plaster Frame)			
Product Code:	181/1312-W		
Order Code:	19326		
	188.8888 (A) (A)		
LED Panel Fran	ne (Surface Mount Frame)		
Product Code:	SM-KIT312-A		

Order Code: 19330

Aluminium Anodised

Product Code:	SM-KIT312-W
Order Code:	19334
Colour:	Satin White

Colour:

Domus 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com Specification subject to change without prior notice.