RADICAL 2 CEILING FAN



Installation Locations: Indoor and outdoor (provided the fan is fully undercover)

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan: Approximately 295mm

Motor:

155mm x 16mm DC motor Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Top Canopy & Downrod: Materials: Die-Cast Aluminium

Available Colours: White, Matt Black and Brushed Aluminium

Blades:

Sizes: 1520mm (60") Materials: Plastic Blade Pitch: 14°

Available Blade Colours:

White, Matt Black, Silver, Bamboo and Koa

Extra Information:

Introduced into the HPI range in 2018 6 Speed remote controller Reversible Matt Black with Bamboo Blade

Standard Canopy Cover: Suitable for flat and pitched ceilings up to 38°

Wall Controller Speed Capacitor Values: N/A

Rotational Diameter: 1520mm (60") blade sweep

Ceiling to top side of the blade: Approximately 215mm

Weight Including Packaging: Complete fan: 6.8kg

Packaging Dimensions (cm): Complete Fan: 79L x 33W x 24H

Accessories (Supplied separately): Extension Down Rod 26mm diameter T-Hook for ceiling roses

Warranty

2 year standard "in home" warranty 3 years extended warranty on motor only (excluding labour)

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

	Speed 1	Speed 2	Speed 3	Speed 4	Speed 5	Speed 6
RPMS	57	88	112	143	166	192
WATTS	4	6.5	10	17	25	37
AIRFLOW: CFM* / CMH*	1568 / 2664	3686 / 6264	5891 / 10008	6696 / 11376	8645 / 14688	9577 / 16272
EFFICIENCY^: (CFM / Watt) / (CMH / Watt)	392 / 666	567 / 964	589 / 1001	394 / 669	346 / 588	256 / 440

* CFM = Cubic Feet per Minute / Cubic Meters per Hour

* Efficiency measured as airflow rate per watt.

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au