



EASY INSTALLATION CLAMP



|       |                                 |              |  |                        |  |            |  |            |  |  |  |  |
|-------|---------------------------------|--------------|--|------------------------|--|------------|--|------------|--|--|--|--|
| 240V  | <b>DIY</b><br>EASY INSTALLATION | 11W<br>800lm |  | 4200K<br>COOL<br>WHITE |  | 25W<br>max |  | 28W<br>max |  |  |  |  |
| LIGHT |                                 |              |  | FAN 18247              |  | FAN 18249  |  |            |  |  |  |  |



Round design exhaust fan with an 800 lumen, 100° beam angle Umbra-II LED as a centre light source.

### FEATURES

- LIGHT: Umbra-II Downlight (IP44 rated)
- EXHAUST: High velocity exhaust fan.
- Easy installation clamps to secure fan into place.
- 150mm side exhaust duct.
- IPX4 water-resistant rating.
- Removable facia for easy cleaning.
- Side exhaust duct to prevent objects falling through.
- Exhaust damper to prevent drafts.
- Requires a switched surface socket for DIY installation.
- 3 Year Replacement Warranty.

| DETAILS   |                 |              | LIGHT     |             |             |                 | EXHAUST     |               |            |                     |                    |       |
|-----------|-----------------|--------------|-----------|-------------|-------------|-----------------|-------------|---------------|------------|---------------------|--------------------|-------|
| MODEL NO. | COLOUR          | CUT-OUT (mm) | LAMP TYPE | WATTAGE (W) | LUMENS (lm) | COLOUR TEMP (K) | WATTAGE (W) | FAN SIZE (mm) | NOISE (dB) | m <sup>3</sup> /MIN | m <sup>3</sup> /HR | L/SEC |
| 18247/05  | WHITE           | Ø240         | SMD LED   | 11          | <b>800</b>  | 4200            | 25          | 124           | ≤45        | ≤4.5                | ≤270               | ≤75   |
| 18247/16  | STAINLESS STEEL | Ø240         | SMD LED   | 11          | <b>800</b>  | 4200            | 25          | 124           | ≤45        | ≤4.5                | ≤270               | ≤75   |
| 18249/05  | WHITE           | Ø290         | SMD LED   | 11          | <b>800</b>  | 4200            | 28          | 144           | ≤45        | ≤5.3                | ≤320               | ≤88   |
| 18249/16  | STAINLESS STEEL | Ø290         | SMD LED   | 11          | <b>800</b>  | 4200            | 28          | 144           | ≤45        | ≤5.3                | ≤320               | ≤88   |