

60min Fire Rated Downlight

The RED intumescent band on the lower section of the downlight and product labelling identify the Superlux 60/60/60 minute fire rated downlight

E27 LED BULB DOWNLIGHT



SD125L-FIRE60

NEW



E27

LED
GLSD-10EWW
Included

- 105 lm/W
- 1050 total lm
- Dimmable
- 10Watts
- 3,000K
- CRI>80
- 240° Beam



SD125L-FIRE60
Energy saving E27 dimmable lamp gives the benefits of newest LED technology with easy maintenance for a long lasting lighting solution

- Thermal cut-off and auto reset function for protection against misuse and overloading
- Lamp not exposed in ceiling cavity
- 3 mounting clips to ensure optimum snug fit to ceiling.

SETTING THE INDUSTRY STANDARD FOR DOWNLIGHT SAFETY

Test Specifications

Tested by BRANZ in accordance with AS1530.4.1997, test report No. FP2971 and FAR1792. Suitable for floor-ceiling systems Gib_ specification No's GBFC15, GBUC15, GBFC30, GBTP30, GBSC30, GBUC30a, GBUC30b, GBSC60, GBFC60, GBTP60 and GBUC60.

60/60/60 Minutes Approval

- 60 Minutes Stability: To prevent collapse of structural (primary) elements during fire.
- 60 Minutes Integrity: To prevent passage of flame or hot gases through fire separations.
- 60 Minutes Insulation: To prevent the transmission of heat to other firecells or adjacent property.

(RW)STC Sound Transmission Class

- Acoustic ratings STC 55, 57 and 58
- For acoustic STC 55 ceilings, space 1.6m minimum
- For acoustic STC 57 and 58 ceilings, space 2.5m minimum

Installation Notes

- For use in 60 minutes floor ceiling systems (also usable for 15 minutes and 30 minutes)
- Only install one fitting in each unsupported section of ceiling lining between timber framing
- Cut 125mm hole not closer than 50mm to timber
- Apply bead of **SD-MASTIC** to flange so as to fill hole gap

Product Certification Warning

BRANZ Fire Tests FP2208, FP2918, FP2998 and FP2971 were conducted exclusively with Superlux manufactured product.

MODEL	CLASS	AIR / MOISTURE TRANSFER	INSULATION	F	Beam Angle	CAVITY DEPTH	SIDE CLEARANCE
SD125FL-FIRE60	CA90	Closed	Side Abutted	Yes	125mm	180mm	25mm