



DIMMABLE SURFACE SERIES LED Surface Mounted Ceiling Lights

PRODUCT FEATURES

- ⊙ Input voltage: 240V AC 50/60Hz
- ⊙ Wattage: 12W & 18W
- ⊙ SMD2835 LED chips
- ⊙ Material: PC body, PMMA lens
- ⊙ Double insulated
- ⊙ Designed in Australia
- ⊙ Dimmable with most trailing edge dimmers
- ⊙ Suitable for 3 wire sensor
- ⊙ Ambient temperature: -20 to 40°C
- ⊙ Large terminal holes for easy connection

LYNX ▶




RECOMMENDED DIMMERS:


BRAND	CODE
CLA - trailing edge	LYNX
Clipsal - universal	32E450UDM
Clipsal - trailing edge	32E450TM
HPM - trailing edge	CAT400T

TECHNICAL DATA

CODE	DESCRIPTION	KELVIN	LUMENS	WATT (W)	CRI	DIAM	DEPTH	CARTON QTY
SURFACE2D	12W WHT FIXED RND WW	3000K	900LM	12	82	∅178mm	40mm	1/20
SURFACE3D	18W WHT FIXED RND WW	3000K	1450LM	18	82	∅225mm	40mm	1/20
SURFACE5D	12W WHT FIXED RND NW	5000K	960LM	12	82	∅178mm	40mm	1/20
SURFACE6D	18W WHT FIXED RND NW	5000K	1550LM	18	82	∅225mm	40mm	1/20



SURFACE2D, 5D



SURFACE3D, 6D

Brochure updated on 14/07/2016

