



SMART START CHARGER - Part No. SJS01G2

12V 400AMP Jump start most vehicles up to 4000cc petrol only. Not Recommended for V-TWIN
Motocycles over 1000cc

- **Power pack:** 134mm x 77.5mm x 32.6mm, weight: 275g
- **Jump start output:** 12V DC, 400A peak / 200 A start
- **Jumper leads:** Jump Start Safe Technology & AWG cable with MOSFET.

Reverse current: >2A max. 18V DC Max. Voltage difference, recognition, short circuit protection, reverse polarity protection, overheat temperature sensor, power pack low voltage indicator, anti-surge protection

- **Safety protection:** Over-discharge, overcharge, resettable overload, digital charging voltage and current recognition, enclosed jump port terminals
- **Battery chargers:** SAA approved 240V AC / 15C DC, 1A wall charger. 12V / 15V DC 800mA car charger
- **Ambient temp:** -20 to 60°C
- **Self discharge:** 10 to 15% over 12 months from full charge (with power switch in 'OFF' position)
- **Device charging:** USB port 5V DC, 2.1A with 4 in 1 USB cable IS8 compliant. Multi volt port 12V, 16V, 19V DC cable + 8 adaptors
- **LED Flashlight:** 3 modes: full on, SOS, emergency flash
- **Packing:** Zip carry bag, 10pcs per outer carton

**JUMP START SAFE™
TECHNOLOGY**



Brochure updated on 19.12.2016