



LED OYSTER LIGHTING

OYS9-12



OYS13



OYS15A, 16



OYS21




FEATURES


- ★ Input voltage: 240V AC 50Hz
- ★ LED panel & driver
- ★ Power factor: 0.9
- ★ Life time: 30,000hrs
- ★ Powder coated metal base
- ★ Large terminal holes for easy connection
- ★ Beam angle: 120°
- ★ PMMA (acrylic) diffuser
- ★ Not suitable for dimming
- ★ IP44
- ★ 3 year replacement warranty

TECHNICAL DATA


CODE	DESCRIPTION	KELVIN	LUMENS	WATT
OYS9	14W SQ WH LED OYSTER 3000K	3000K	980	14
OYS10	14W SQ WH LED OYS 5000K	5000K	1050	14
OYS11	28W SQ WH LED OYS 3000K	3000K	1900	28
OYS12	28W SQ WH LED OYS 5000K	5000K	2000	28
OYS13	28W SIL/CLR TRIM RND LED OYS 3000K	3000K	1400	28
OYS15A	14W BR/AL RND LED OYS 3000K	3000K	800	14
OYS16	14W BR/AL RND LED OYS 5000K	5000K	850	14
OYS21	28W CHROME TRIM RND LED OYS 5000K	5000K	1650	28




DIMENSIONS OF OYS9-10
PLATE: 250X250mm




DIMENSIONS OF OYS11-12
PLATE: 350X350mm



DIMENSIONS OF OYS13
PLATE OD: Ø350mm



DIMENSIONS OF OYS15-16
PLATE OD: Ø260mm



DIMENSIONS OF OYS21
PLATE OD: Ø300mm

UPDATED ON 29.11.2016