



DOUBLE ENDED METAL HALIDE GLOBES

- Input voltage: 240V AC with control gear
- Wattage: 35W, 70W & 150W
- Reduced UV output
- Excellent colour rendering
- High intensity light output

10,000 HRS

1 YEAR WARRANTY



CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS	
		BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	LENGTH (mm)	CARTON QTY
35W							
CLAMHD35W3000K	35W RX7S DOUBLE ENDED MH 3000K	RX7S	3000	2800	35	114	1/12
CLAMHD35W4000K	35W RX7S DOUBLE ENDED MH 4000K	RX7S	4000	2800	35	114	1/12
CLAMHD35W5000K	35W RX7S DOUBLE ENDED MH 5000K	RX7S	5000	2800	35	114	1/12
70W							
CLAMHD70W4000K	70W RX7S DOUBLE ENDED MH 4000K	RX7S	4000	4900	70	114	1/12
CLAMHD70W5000K	70W RX7S DOUBLE ENDED MH 5000K	RX7S	5000	4900	70	114	1/12
150W							
CLAMHD150W3000K	150W RX7S DOUBLE ENDED MH 3000K	RX7S	3000	11250	150	132	1/12
CLAMHD150W4000K	150W RX7S DOUBLE ENDED MH 4000K	RX7S	4000	11250	150	132	1/12

Brochure updated on 19.12.2016

