

LED Exterior Surface Mounted Wall Lights







OBLONGO01

OBLONGO02



OBLONGO03

OBLONGO04





OBLONGO05

OBLONGO06



• Input voltage: 220-240V AC 50/60Hz

• Inbuilt driver input current: 0.11A

• Inbuilt driver output current: 500mA

Wattage: 5W

• Power factor: ≥0.35

• 1pc CREE COB LED chip

• Concrete with die cast aluminium back plate & SS clips

• Not suitable for dimming



120 MM

BACK PLATE





IP65 Rated



PART NO.	DESCRIPTIONS	KELVIN (K)	LUMENS (LM)	CRI	WATT	WEIGHT (KG)	BOX (cm)	CARTON QTY
OBLONGO01	WALL LED 240V S/M Cement Coloured Rect Up/Dn	3000	500	80	5	2.3	18x18x39.5	6
OBLONGO02	WALL LED 240V S/M Replica White Marble Rect Up/Dn	3000	500	80	5	2.3	18x18x39.5	6
OBLONGO03	WALL LED 240V S/M Replica Black Marble Rect Up/Dn	3000	500	80	5	2.3	18x18x39.5	6
OBLONGO04	WALL LED 240V S/M Replica Dark Wood Rect Up/Dn	3000	500	80	5	2.3	18x18x39.5	6
OBLONGO05	WALL LED 240V S/M Replica Light Wood Rect Up/Dn	3000	500	80	5	2.3	18x18x39.5	6
OBLONGO06	WALL LED 240V S/M Replica Red Brick Rect Up/Dn	3000	500	80	5	2.3	18x18x39.5	6

UPDATED ON 30.01.2018

Website: www.clalighting.com.au

Tel: (02) 9938 7100 | Fax: (02) 9938 7115 | Email: sales@clalighting.com.au Follow us: facebook.com/CLALighting

