

MINI ROUND



FLAT ROUND



MINI OVAL



FLAT OVAL



240V	SMD LED	4200K COOL WHITE	38°	32°	CRI(Ra) >80	POWER FACTOR 0.81	90-95mm	IC-4	1m
			MINI TRIM (RND/OVAL)	FLAT TRIM (RND/OVAL)					

Increased visual comfort with a deep-recessed design and tilting head to provide a contained and glare-free beam angle, ie above beds.

### FEATURES

- 4 configurations in 1.
- Rated for IC-4 Abutted and Covered usage to allow for covering with thermal insulation.
- Gimbal head downlight.
- Diecast aluminium trims and heatsink.
- Includes 4 trims (2 x round & 2 x oval).
- Multiple beam angles depending on engine position and trim.
- High efficiency LED SMD Array.
- External Australian approved dimmable LED driver.
- Long lasting up to 30,000 hours<sup>1</sup>.
- 1m flex & plug fitted.
- 3 Year Warranty.

### MAIN APPLICATIONS

All interior residential rooms.

MODEL NO.	WATTAGE (W)	LUMENS MINI TRIM (RND/OVAL) (lm)	LUMENS FLAT TRIM (RND/OVAL) (lm)	FITTING COLOUR
19909/05	8	800	600	WHITE

<sup>1</sup> Actual life may vary depending on individual circumstances.



Mini Round	Flat Round	Mini Oval	Flat Oval
5234lx 0.3m	5448lx 0.2m	982.4lx 0.6m	4583lx 0.3m
1308lx 0.6m	1362lx 0.5m	245.6lx 1.1m	1146lx 0.6m
581.5lx 0.9m	605.4lx 0.8m	109.2lx 1.7m	509.2lx 0.9m
327.3lx 1.2m	340.5lx 1.1m	61.40lx 2.2m	286.4lx 1.2m
209.4lx 1.5m	217.9lx 1.4m	39.30lx 2.8m	183.3lx 1.5m

