



PICTOGRAMS INCLUDED



| | | | | | | | | |
|--------------|------------------------|----------------------|--|--|------------|------------|-----------------------|--------------------|
| 240V 50Hz | 5W TOTAL WATTAGE | 2W MAINTD LAMP | | | CRI >80 | Ta 40°C | C0: E2.0 C90: E1.6 | AS/NZS APPROVED |
|--------------|------------------------|----------------------|--|--|------------|------------|-----------------------|--------------------|

The One-Box is a general purpose, double or single-sided interior ceiling or wall mounted exit sign. For use at doorway, stairways, corridors and intersection on an emergency escape route. The One-Box exit sign incorporates an integral emergency 2 hour battery pack that permits self-powered operation during power outages.

FEATURES

- Compliant to AS/NZS 2293
- 50,000 Hour average life rated LED modules
- Surface-mount Ceiling or Wall
- Injection moulded polycarbonate housing and acrylic diffuser with pictogram legends
- Viewing distance 24M
- High density storage LiCoO2 batteries
- Diffuser & pictogram inserts included
- IP20 rating
- 2 Hour duration period
- TA40 - maximum thermal ambient operating temperature
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous

APPLICATIONS

Doorways, stairways, corridors and intersections on an emergency escape route.

CLASSIFICATION & SPACING DISTANCE

| Model | Mounting Height in Metres | | | | | | | | | | |
|-------|---------------------------|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| | Plane | Class | 2.1 | 2.4 | 2.7 | 3.0 | 3.6 | 4.0 | 4.5 | 5.0 | 6.0 |
| 19874 | C0 | E2.0 | 5.2 | 5.2 | 5.4 | 5.2 | 5.0 | 4.6 | 4.8 | 4.0 | - |
| | C90 | E1.6 | 4.8 | 4.8 | 4.8 | 4.4 | 4.2 | 3.8 | - | - | - |

| MODEL NO. | MAINTAINED LAMP WATTAGE (W) | NON-MAINTAINED LAMP WATTAGE (W) | FITTING COLOUR |
|-----------|-----------------------------|---------------------------------|----------------|
| 19874/.. | 2 | - | /05-WHITE |

