



240V | MINIMUM | MAXIMUM | LOAD | LOAD | SOW

Our universal dimmers are a compact, modular dimming mechanism rated at 350W, and designed for universal load compatibility. The unit utilises powerful and sophisticated dimming technology to provide full control of almost any type of load. Used to control loads such as LED, incandescent lamps, 240V halogen lamps, dichroic lamps and low voltage lighting that uses iron-core or electronic transformers.

The Push Button model incorporates on/off switching and dimming control into one mechanism. The dimming performance is optimised to ensure smooth, linear dimming across the control range.

The Rotary Dial model is a separately switched unit that utilises sophisticated dimming technology to provide full control of a wide range of load types.

- Dimming: 2% to 100%*.
- Design & optimised for dimmable LED lamps & fittings.
- Fits into standard Clipsal® & HPM® branded wall plates.
- 2 wire design*.
- Suitable for most dimmable 240V fixtures and globes*.
- Also works with most magnetic or dimmable electronic transformers*.
- Soft start for improved lamp life.
- Detects the load type and selects either leading or trailing edge as required.
- 12 Month Warranty.

* Load dependent. Final performance may vary according to actual LED globe and transformer/driver used. Must be installed by a licensed electrician. Not suitable for fans and other inductive loads.

MODEL NO.	ТҮРЕ	FITTING COLOUR	BARCODE
18828/05	Push Button	WHITE	9 312641 188285 >
18829/05	Rotary Dial	WHITE	9 312641 188292 >



Brilliant Lighting (Aust) Pty Ltd www.brilliantlighting.com.au