



PICTOGRAMS INCLUDED



| | | | | | | | | | | |
|--------------|------------------------|----------------------|-----------------------|--|--|--|------------|------------|-----------------------|--------------------|
| 240V 50Hz | 5W TOTAL WATTAGE | 2W MAINTD LAMP | 1W NON-MTD LAMP | | | | CRI >83 | Ta 40°C | CO: E5.0 C90: E2.0 | AS/NZS APPROVED |
|--------------|------------------------|----------------------|-----------------------|--|--|--|------------|------------|-----------------------|--------------------|

The Blade is a stylish Exit Sign ideal for emergency lighting application where aesthetics are everything. Double or single-sided interior recessed mounted exit sign for use at doorway, stairways and corridors and intersection on an emergency escape route. The Blade incorporates an integral emergency 2 hour battery pack that permits self-powered operation during power outages.

FEATURES

- Compliant to AS/NZS 2293
- 50,000 Hour average life rated LED modules
- Recessed & Surface mount options
- Injection moulded polycarbonate housing and acrylic diffuser with pictogram legends
- Viewing distance 24M
- High density storage LiCoO2 batteries
- Diffuser & pictogram inserts included
- IP20 rating
- Additional 1W Non-Maintained downlight during mains power outage
- Fully tested & compliant with Australian Standards
- 2 Hour duration period
- TA40 - maximum thermal ambient operating temperature
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous

APPLICATIONS

Commercial office areas, hotels, shopping centres, apartments & hospitals.

CLASSIFICATION & SPACING DISTANCE

| | | Mounting Height in Metres | | | | | | | | | |
|-------|-------|---------------------------|-----|-----|-----|-----|-----|-----|-----|-----|--|
| Plane | Class | 2.1 | 2.4 | 2.7 | 3.0 | 3.6 | 4.0 | 4.5 | 5.0 | 6.0 | |
| C0 | E5.0 | 6.6 | 7.2 | 7.4 | 7.8 | 8.0 | 8.2 | 8.4 | 8.4 | 8.2 | |
| C90 | E2.0 | 5.2 | 5.2 | 5.4 | 5.0 | 4.6 | 4.8 | 4.0 | - | - | |

| MODEL NO. | MOUNT TYPE | MAINTAINED LAMP WATTAGE (W) | NON-MAINTAINED LAMP WATTAGE (W) | FITTING COLOUR |
|-----------|------------------------|-----------------------------|---------------------------------|----------------|
| 19878/.. | RECESSED | 2 | 1 | /05-WHITE |
| 19880/.. | SURFACE | 2 | 1 | /05-WHITE |
| 19893/.. | SURFACE MOUNT BOX ONLY | | | /05-WHITE |

