



240V 50Hz	40W MAINTD LAMP	6W SUSTAIN LAMP	SMD LED	4200K COOL WHITE		CRI >80	IK08	MAINTAINED	AS/NZS APPROVED
--------------	-----------------------	-----------------------	---------	------------------------	--	------------	------	------------	--------------------

19992
ONLY

The Stellar LED battens feature an IP65 weather-resistant rating and sustained mode operation. The Stellar luminaire incorporates an emergency 2 hour battery pack that permits self-powered operation during power outages.

FEATURES

- Corrosion resistant, IP65 weatherproof polycarbonate body
- Vandal-resistant IK08 rated.
- UV stabilised high impact polycarbonate cover.
- Stainless steel mounting brackets for easy installation.
- Compliant to AS/NZS 2293
- Ceiling mount.
- C0: D25; C90: D63 classifications
- High density storage LiCoO₂ (3600mAh) batteries
- 2 Hour duration period
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous

APPLICATIONS

Wet rooms, commercial and interior applications, coastal environment, apartments, shopping centres, carparks, stairwells, hospitality, prisons and hospitals.

CLASSIFICATION & SPACING DISTANCE

		Mounting Height in Metres									
Plane	Class	2.1	2.4	2.7	3.0	3.6	4.0	4.5	5.0	6.0	
C0	D25	14.2	14.7	15.3	15.7	16.5	16.9	17.3	17.7	18.1	
C90	D63	19.4	20.3	21.1	21.8	23.0	23.7	24.5	25.2	36.4	

MODEL NO.	PRODUCT	FITTING COLOUR
19992/08	EMERGENCY MODEL	GREY
19998/08	NON-EMERGENCY MODEL	GREY

