THE DUET

COMBINATION RECESSED OR SURFACE MOUNT CCT DOWNLIGHTS





The versatile mounting options of the Duet offer variable and professional lighting solutions for shops, hotels and offices.

FEATURES

- Change between Warm White (3000K), Cool White (4000K) & Daylight (6000K) via a switch on the back of the downlight.
- Rated for IC-F Abutted and Covered usage to allow for covering with thermal insulation.
- Wide 100 degree beam angle.

20828


- Super slim SAA approved internal non-dimmable LED driver.
- Long lasting up to 30,000 hours1.
- 0.6m flex & plug fitted.
- Three common cut-out sizes to suit most Retrofit applications.
- Includes all fittings to convert to either recessed or surface mount.
- 3 Year Warranty.

MAIN APPLICATIONS

All interior domestic and commercial rooms.

MODEL NO.	WATTAGE (W)	LUMENS @ 3000K (lm)	LUMENS @ 4200K (lm)	LUMENS @ 6500K (lm)	CUT-OUT (mm)	FITTING COLOUR
20827/05	12	800	1000	900	145	WHITE
20828/05	18	1400	1600	1600	195	WHITE
20829/05	24	1600	2000	1800	215	WHITE

Actual life may vary depending on individual circumstances



Ø245

Ø240